

DECLARATION OF PERFORMANCE
No RW-CEE-DoP-2028/B/17/w1

- | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>1. Unique identification code of the product-type:
RW-CEE-2028</p> <p>2. Intended use: Thermal insulation products for buildings (ThIB).</p> <p>3. Manufacturer: ROCKWOOL® a.s. Cihelni 769, Skřečovi,
735 31 Bohumín</p> | <p>4. System/s of AVCP: System 1 and System 3</p> <p>Harmonised standard: EN 13162:2012+A1:2015</p> <p>5. Notified body No 1390 Centrum stavebního inženýrství a.s. Praha</p> <p>6. Declared Performance in the Table 1 and Table 2:
MW-EN 13162-T6-DS(70,-)-CS(10)20-SDI¹⁾-WS-WL(P)-CP(4)-MU1</p> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Table 1

Essential Characteristics	Performance	Declared value / NPD ¹⁾	Harmonized technical specification
Thermal resistance	Thermal resistance R ₀ Thickness d _N	see Table 2	EN 13162:2012+A1:2015
	Thermal conductivity λ ₀	0,037 W/mK	
	Ti ²⁾ Thickness	T6	
Reaction to fire	Euroclasses – Reaction to fire (RfF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation ²⁾	Durability characteristics Reaction to fire (RfF) product	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation ²⁾	Thermal resistance R ₀ and thermal conductivity λ ₀ (W/mK)	see Table 2 0,037 W/mK	
	Durability characteristics	DS(70,-)	
Compressive strength	Compressive stress CS(10) ³⁾ , CS(10/Y) ³⁾ (kPa)	CS(10)20	
	Point load PL(5) ³⁾ (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR ³⁾ (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
	Water permeability	Short term water absorption WS (≤1 kg/m ²) Long term water absorption WL(P) (≤ 3 kg/m ²)	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	MU1	
	Impact noise transmission index (for floors)	Dynamic stiffness SD ³⁾	
Thickness, d _L		NPD	
Compressibility c		CP(4)	
Air flow resistivity AF _r ³⁾		NPD	
Acoustic absorption index	Sound absorption AW ³⁾	NPD	
Direct airborne sound insulation index	Air flow resistivity AF _r ³⁾	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances to the indoor environment	NPD	

¹⁾ No performance determined (NPD), ²⁾ no change with time, ³⁾ * Indicates relevant class of level or declared value.

Table 2

d _N (mm)	20	30	40	50	60	-	-	-	-	-	-	-	-	-	-	-	-
R ₀ (m ² /KW)	0,50	0,80	1,05	1,35	1,60	-	-	-	-	-	-	-	-	-	-	-	-

This declaration of performance is available on the website dop.rockwool.com

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Pawel Pomykala
Factory Manager

Bohumín 2018-04-20



ROCKWOOL a.s., Bohumín
Pawel Pomykala, factory manager

